

## Aerial Lift Attachments

Aerial hoists can accommodate numerous tasks involving high and tough reaching places. Normally utilized to carry out daily maintenance in buildings with elevated ceilings, trim tree branches, elevate burdensome shelving units or repair telephone cables. A ladder might also be used for some of the aforementioned jobs, although aerial platform lifts provide more safety and strength when correctly used.

There are a couple of distinctive designs of aerial hoists available, each being able to perform moderately unique jobs. Painters will often use a scissor lift platform, which can be utilized to get in touch with the 2nd story of buildings. The scissor aerial platform lifts use criss-cross braces to stretch out and lengthen upwards. There is a table attached to the top of the braces that rises simultaneously as the criss-cross braces lift.

Container trucks and cherry pickers are another type of aerial lift. They contain a bucket platform on top of a long arm. As this arm unfolds, the attached platform rises. Forklifts use a pronged arm that rises upwards as the handle is moved. Boom lift trucks have a hydraulic arm which extends outward and elevates the platform. Every one of these aerial lifts call for special training to operate.

Through the Occupational Safety & Health Association, also labeled OSHA, training courses are on hand to help make sure the workforce satisfy occupational values for safety, machine operation, inspection and maintenance and machine cargo capacities. Workers receive certification upon completion of the lessons and only OSHA certified employees should run aerial lift trucks. The Occupational Safety & Health Organization has developed guidelines to maintain safety and prevent injury when utilizing aerial platform lifts. Common sense rules such as not using this machine to give rides and ensuring all tires on aerial hoists are braced in order to prevent machine tipping are observed within the guidelines.

Sadly, figures show that more than 20 operators die each year when working with aerial hoists and 8% of those are commercial painters. The majority of these mishaps are due to inadequate tire bracing and the lift falling over; for that reason many of these deaths had been preventable. Operators should make certain that all wheels are locked and braces as a critical safety precaution to prevent the machine from toppling over.

Marking the surrounding area with visible markers need to be utilized to protect would-be passers-by in order that they do not come near the lift. In addition, markings should be placed at about 10 feet of clearance amid any power lines and the aerial hoist. Hoist operators should at all times be well harnessed to the hoist while up in the air.